




360



360° fisheye panoramic with IR



Versatile, robust and sleek, fit for both the hardest outdoor and discreet indoor setups



12MP image sensor



Built-in AI video and audio analytics and on-device storage



Factory-installed certificates backed by a trusted platform module (TPM)



Designed and developed in Norway and the UK

Image sensor

12MP

Image sensor size format

1/2.3"

Effective resolution

9MP

Lens

Aperture: $f/2.0$

Fixed focus

Focus distance: 0.5m - ∞

IR night vision

Automatic night mode

IR-cut filter

IR range: 20m

850 nm IR LED

Minimum illumination in color mode

0.4lux

Field of view

>180°

Maximum resolution & Frame rate

3000x3000@30fps

Dynamic range

Multi-exposure line-based HDR

Video compression

H.265, H.264, Motion JPEG

Audio

Microphone array (4x microphones)

AI audio event classification

Audio source localization

Security

Factory-installed certificates, no default passwords, mandatory access authentication, HTTPS/TLS encryption

Network protocols

IPv4, HTTPS, TLS, DNS, mDNS, DNS-SD, NTP, RTSP, RTP, RTCP, ICMP, DHCP, ARP

Streaming protocols: RTP/UDP, RTP/

RTSP/HTTPS/TCP

Power source

PoE+ (802.3at Type 2)

For installation only: USB-C (1.5A mode)

Power consumption

Typical: 5 W

Max without heater: 12.95 W

Max with heater: 23 W

Storage

MicroSD, SDXC UHS-I

Connection

802.3ab 10/100/1000 Gigabit Ethernet

USB-C for preview and setup

Installation aid

Automatic wall and ceiling detection.

Flexible bracket, mounts to standard back boxes. Refer to technical drawing.

Impact resistance

IK10 (IEC/EN 62262)

Ingress protection

IP66 (IEC/EN 60529)

Temperature

Operating: -40°C to +50°C

Storage: -40°C to +60°C

Heater: 9.6W

Physical characteristics

Dimensions: 152x152x77mm

Weight: 1.1 kg

Body: Aluminum

EMC


EN 55032, EN 61000-3-2/-3, EN 55024, EN 55035, EN61000-6-2/-4, FCC Part 15B, ICES-003 Issue 6

Safety

IEC60950-1, IEC62368-1, IEC60950-22, UL/CSA60950-1, UL/CSA 62368-1, UL E164374, NOM-019, IEC62471(IR LED)


Technical drawings

360, side view



Scale 1:2

Mounting bracket, top view



Scale 1:2

	Designation	Dimension (mm)	Dimension (inch)
A	Octagon	62.9 x 62.9 (88.9 diagonal)	2.47 x 2.47 (3.50 diagonal)
B	4" Square Box	85.5 x 85.5 (120.9 diagonal)	3.36 x 3.36 (4.76 diagonal)
C	Single Gang	84.1	3.31
D	Double Gang	84.1 x 46	3.31 x 1.81
E	EU Ceiling Box	70	2.76
F	EU Outlet Box	60	2.36

Ordering information

Ava Dome

Product ID	Onboard retention	Deployment	Color
360-W-30	30 days	Aware Cloud	White
360-B-30	30 days	Aware Cloud	Black
360-W-60	60 days	Aware Cloud	White
360-B-60	60 days	Aware Cloud	Black
360-W	no	Aware on-prem	White
360-B	no	Aware on-prem	Black

Accessories

Product ID	Product name	Color
ACC-PEN-CAP-W	Pendant mounting cap	White
ACC-PEN-CAP-B	Pendant mounting cap	Black
ACC-MNT-ARM-W	Wall mount arm	White
ACC-MNT-ARM-B	Wall mount arm	Black
ACC-POL-BRA-W	Pole bracket	White
ACC-POL-BRA-B	Pole bracket	Black
ACC-CRN-BRA-W	Corner bracket	White
ACC-CON-A34-W	Conduit adapter 3/4"	White
ACC-CON-A34-B	Conduit adapter 3/4"	Black
SVCS-CAM-W5YR	5-year total warranty	—