AerPOS

15inch or 17inch High Performance POS System



AerPOS

We aim to exceed your expectations by providing high quality, reliable products with state of the art designs.

AerPOS is an elegant and powerful all-in-one system, designed to be used in the toughest retail and hospitality environments. It is a very durable and compact system that fits beautifully on any point of sale counter. The modular design features also ensures high serviceability.

Add-on Devices

All AerPOS add-on devices use a USB interface for reliability, simple installation and maintenance.

USB I/O is on the right side of the display



Peripherals





Smart Fan detects CPU temperature and adjusts fan speed automatically



Standard Colors: Black + Silver; Black + Red; White + Silver



The integrated customer display can be turned and tilted for the best viewing angle.



11.6inch second display with bracket



MSR

15inch second display (pole type)



■ ▲ ▼ ७

One-step operation for quick access to hard disk or SSD



The display can be easily removed for easy maintenance



CPU module can be extracted for efficient upgrades and maintenance



Specifications

Model	AP-3615	AP-3617	AP-3625
Processor	Intel® Celeron® G540, 2.5Ghz Intel® Core i3-2120, 3.3Ghz Intel® Core i5-3550S, 3.0Ghz		Intel® Celeron® B810, 1.6Ghz Intel® Core i5-2510E, 2.5Ghz (vPro)
System Memory	2GB Standard, Maximum 8GB (1x204-pin DDR3)		
Power Supply	150W (12V / 12.5A) External Power Adaptor		
Storage Device	1 x 2.5" SATA HDD or SSD		
Chipset	Intel® H61		Intel® QM67
Speaker	Internal Speaker 2W x 2		
Construction	Aluminum Die-casting + Plastic + Glass		
Housing Color	Black with Silver Trim; Black with Red Trim; White with Silver Trim		
Touch LCD Display			
Size / Resolution	15" TFT-LCD / 1024 X 768	17" TFT-LCD / 1280 X 1024	15" TFT-LCD / 1024 X 768
Brightness (Backlight Type) & Touch Screen	250 cd/m² (CCFL); 5-Wire Resistive Touch	250 cd/m ² (LED); 5-Wire Resistive Touch / Projected Capacitive Touch	250 cd/m² (CCFL); 5-Wire Resistive Touch
	350 cd/m2 (LED) with Tempered Glass; Projected Capacitive Touch	350 cd/m² (LED); 5-Wire Resistive Touch / Projected Capacitive Touch	350 cd/m² (LED) with Tempered Glass; Projected Capacitive Touch
I/O Ports			
Serial Port	4 x External: COM 1, COM 2 (DB9), COM 3, COM 4 (RJ45)		
USB Port	5 x External (4 Rear + 1 Side)		
Cash Drawer Port	1 x RJ11 (12V)		
LAN Port	1 x RJ45 Giga LAN		
Audio Port	1 x Line Out, 1 x Mic In		
Video Port	1 x VGA		
DC Output	1 x 12V DC Jack 2.5 mm		
Optional I/O Board			
Type A	Serial Port: COMA (DB9); 12V Powered USB Port x 1; 2 x USB		
Type B	Powered USB Port: 24V x 1		
Type C	Powered USB Port: 24V x 1; 12V x 2		
OS Supported			
Windows	Windows XP, POSReady 2009, Windows 7, POSReady 7		
Physical Dimensions			
Dimensions (W x H x D)	370 x 360 x 222 mm	410 X 386 X 222 mm	370 x 360 x 222 mm
Carton Dimensions (W x H x D)	450 x 480 x 310 mm	530 x 540 x 370 mm	450 x 480 x 310 mm
Weight	7.1kg (Net), 9.1kg (Gross)	10kg (Net), 12kg (Gross)	7.1kg (Net), 9.1kg (Gross)